

BEST AVAILABLE COPY

Application No.: 10/735,602

Docket No.: JCLA10516

In The Claims:

Please amend the claims as follows:

Claim 1. (currently amended) A method for delivering a biological material using a gene gun, comprising:

providing the gene gun comprising a pressurized chamber, a sprayer, a controller valve and a material delivery system;

placing a sample solution into the material delivery system, wherein the sample solution comprises at least the biological material;

triggering the gene gun and providing a gas through ~~the control of the controller~~ valve to the pressurized chamber until the gas establishes a pressure;

releasing the sample solution from the material delivery system, so that the sample solution is accelerated by the gas in the pressurized chamber; and

discharging the sample solution out of the sprayer, wherein the sprayer includes a spray nozzle and a spray tube, and the spray nozzle comprises an interior contour, wherein the interior contour of the spray nozzle comprises a diverging part and a converging part and the spray tube is a diverging straight tube, so that a discharge speed of the sample solution is supersonic and the biological material is evenly injected into a target.

Claim 2. (original) The method of claim 1, wherein the biological material is a nucleic acid.

Claim 3. (original) The method of claim 1, wherein the biological material is a protein.

Application No.: 10/735,602

Docket No.: JCLA10516

Claim 4. (original) The method of claim 1, wherein the biological material is a virion.

Claim 5. (original) The method of claim 1, wherein the biological material is a vaccine.

Claim 6. (original) The method of claim 1, wherein the biological material is an immunogen for cancer immunotherapy.

Claim 7. (original) The method of claim 1, wherein the sample solution is accelerated to a speed of 200-300 m/s by the gas.

Claim 8. (currently amended) The method of claim 1, wherein a pressure at ~~an outlet of the sprayer~~ the sprayer's outlet is about 1 atmospheric pressure.

Claim 9. (original) The method of claim 1, wherein the spray nozzle further comprises a spray neck positioned between the diverging part and the converging part, and a range of the interior contour of the converging part includes:

$rt < Rt < 2rt$, wherein Rt represents a curvature radius of the converging part, rt is a radius of the spray neck; and

wherein $\Theta < 15$ degrees, wherein Θ is an angle between the diverging part and a center axis of the spray tube.

Application No.: 10/735,602

Docket No.: JCLA10516

Claim 10. (original) The method of claim 1, wherein the gas includes a nitrogen gas or a helium gas.

Claim 11. (currently amended) A method for gene transformation by using a gene gun, comprising:

providing the gene gun comprising a pressurized chamber, a sprayer, a controller valve and a material delivery system;

placing a sample solution into the material delivery system, wherein the sample solution comprises at least a nucleic acid;

triggering the gene gun and providing a gas through ~~the control of~~ the controller valve to the pressurized chamber, wherein the gas is a nitrogen gas or a helium gas;

releasing the sample solution from the material delivery system after the gas in the pressurized chamber establishes a pressure, so that the sample solution is accelerated by the gas in the pressurized chamber; and

discharging the sample solution out of the sprayer, wherein the sprayer includes a spray nozzle and a spray tube, and the spray nozzle comprises an interior contour, wherein the interior contour of the spray nozzle comprises a diverging part and a converging part and the spray tube is a diverging straight tube, so that a discharge speed of the sample solution is supersonic and the biological material is evenly injected into a target.

Application No.: 10/735,602

Docket No.: JCLA10516

Claim 12. (original) The method of claim 11, wherein the sample solution is accelerated to a speed of 200-300 m/s by the gas.

Claim 13. (currently amended) The method of claim 11, wherein a pressure at ~~an outlet of the sprayer~~ the sprayer's outlet is about 1 atmospheric pressure.

Claim 14. (original) The method of claim 11, wherein the spray nozzle further comprises a spray neck positioned between the diverging part and the converging part, and a range of the interior contour of the converging part includes:

$r_t < R_t < 2r_t$, wherein R_t represents a curvature radius of the converging part, r_t is a radius of the spray neck; and

wherein $\Theta < 15$ degrees, wherein Θ is an angle between the diverging part and a center axis of the spray tube.

Claim 15. (original) The method of claim 1, wherein the nucleic acid is used for gene therapy.